

Aluminum Flood Gates & Demountable Barriers

Tucsenberg
2026.08
TB-AG-SPEC - v2

TB-AG series - stacked planks, EPDM seals, three post types, custom-cut to your opening schedule

180 mm

plank profile height

6063-T6

alloy / temper

1.8 m

standard stacked height

12 h

reply target

Measure once, install the fixings once; from then on the opening seals in minutes, every season, with planks that stack between posts and store flat the rest of the year. We supply the planks, posts, seals and spares factory-direct, custom-cut to your opening schedule. Depending on your market you may know this category as flood boards (UK), removable flood panels or garage flood barriers - same system, same parts.

Specifications confirmed at quotation

Parameter	Value
Plank profile height	180 mm
Alloy / temper	6063-T6
Wall thickness	≥2.0 mm
Plank weight	typical 4.5-6.5 kg/m class - confirmed per profile at quotation
Standard protection height	up to 1.8 m stacked; above on engineering review
Span between posts	height-dependent - up to ~3 m single span at typical heights; post count quoted from width × protection height
Seals	EPDM, replaceable
Post options	wall-mount / ground-socket / freestanding
Surface finish	mill finish standard; anodised on request

Custom-cut, always

- Custom-cut, always. Every order is cut to your opening schedule - send widths and heights (photos and drawings welcome), we deliver planks per opening, labelled. From tested profiles, per approved drawings; we don't do site engineering or stamped drawings, and we say so upfront.
- Your measurements, our cutting. You survey the opening; we cut, label and pack per opening. Your installer unpacks kit #3 for door #3.
- Spare-parts continuity - seals, clamps, single planks stay orderable for years. Your installed base stays serviceable through you.

Honest boundaries

- One boundary before anything else: a flood gate protects a defined opening.
- And rain can still fall or blow in behind any barrier, so plan for a pump or a drain on the protected side.

Ordering

- Send your opening schedule - width × height per opening, mounting surface, photos if you have them.
- 30% deposit, 70% before shipment, by T/T. For custom orders, terms are agreed per order and confirmed with your quotation.
- 3 years on materials and workmanship. Custom-cut items are final sale - measure carefully, and use our RFQ review before you commit.
- Cut-to-order production confirmed at quotation. In-stock standard planks: ships in 2-7 days.

We reply within 12 hours. If the details are sufficient, the reply includes a quote. Otherwise, we ask only for the missing essentials.